

Data-Sheet USB Relais 1



Easily connects digital in- an output lines without additional hardware
connection is done without screwing or soldering using clemp connectors
up to 4 potential free changeer outputs channels

High quality Finder Relais® switches current of 2.0A and voltage to 30V
The dimensions of the housing are: 90mm x 40mm x 28mm

Multiple USB devices at a single PC controlled by unique the serial number
Application Program Interface (DLL) for easy integration in user applications

The control software [ClewareControl](#) for timed switching, [USBswitch](#) with a graphical user interface and [USBswitchCmd](#) for switching via
command call is ready for [download](#).

Network enabled Software ClewareControl - switching from remote PC possible

No driver installation needed with Windows® variants that support USB.

(® Microsoft Windows is a registered trademark of the Microsoft Corporation.)

Can also be used under different [Ubuntu](#) support

RoHS, CE & EN60950 conform / IP30

For indoor use only

4 years warranty

Made in Germany

Customs Tariff number: 85423190

Country of origin: Germany

Item details:

Version	EAN number	Weight/g	Length/mm	Height/mm	Width/mm
USB Relais 1	4251566201165	90	88	25	39
USB Relais 1 L	4251566201172	120	"	"	"
USB Relais 4	4251566201226	90	"	"	"
USB Relais 4 L	4251566201233	120	"	"	"