




FITTING INSTRUCTIONS FOR LP0102BK LICENCE PLATE BRACKET
SUZUKI GSX-R600 2011



THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED BELOW.
DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

THE PARTS SHOWN MAY BE REPRESENTATIVE ONLY (FOR CLARITY OF INSTRUCTIONS ONLY)



R&G Racing
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



LEGEND

- ITEM 1 = LICENCE PLATE BRACKET (TB0102BK) (x1).
- ITEM 2 = CONNECTORS (BULLET CONNECTORS FOR LICENCE PLATE ILLUMINATOR).
- ITEM 3 = LICENCE PLATE ILLUMINATOR (LA0002) (x1).
- ITEM 4 = LIGHT SHROUD (LH0004) (x1).
- ITEM 5 = 150mm LENGTH OF HEAT SHRINK (x1).
- ITEM 6 = REFLECTOR (x1).
- ITEM 7 = CABLE CLIPS (x2).

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

TOOLS REQUIRED

- Set of metric Allen keys to include 4 and 5mm A/F sizes.
- Socket set to include 6,10 and 12mm A/F sockets and wrench.
 - Phillips screwdriver.
 - Electrical pliers/crimps.



PICTURE 1



PICTURE 2

FITTING INSTRUCTIONS

- REMOVE SEAT.
- REMOVE PILLION SEAT.
- UNDO AND REMOVE ALL PILLION SEAT COWL BOLTS AND REMOVE PILLION SEAT COWL.
- REMOVE RIGHT HAND INDICATOR HOUSING FOR ACCESS TO LICENCE PLATE ILLUMINATOR WIRING SOCKET (SEE PICTURE 2).
- DISCONNECT LICENCE PLATE ILLUMINATOR WIRING SOCKET.
- REMOVE THE FOUR BOLTS SECURING THE ORIGINAL LICENCE PLATE BRACKET (SEE PICTURE 1) AND GENTLY LOWER WHILE ENSURING THE WIRING PLUGS DO NOT SNAG ON ITS WAY THROUGH THE ORIGINAL ROUTING (SEE PICTURE 3).
- FIT NEW LICENCE PLATE ILLUMINATOR TO NEW LICENCE PLATE BRACKET (SEE PICTURE 4). WE SUGGEST CUTTING AND REUSING ORIGINAL PLUG SOCKET. PROTECT THE WIRES USING HEAT SHRINK FROM KIT.

R&G Racing


Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



THE ORIGINAL GREY WIRE -----NEW RED WIRE.
THE ORIGINAL BLACK/WHITE WIRE (EARTH) -----NEW BLACK WIRE.

- **PLEASE NOTE YOU WILL NEED TO GLUE THE LIGHT SHROUD TO THE LED LICENCE PLATE ILLUMINATOR BEFORE FITTING USING SUPER GLUE (SEE PICTURE 4).**



PICTURE 3



PICTURE 4

- FEED THE LICENCE PLATE ILLUMINATOR WIRES THROUGH THE HOLE IN THE ANGLED FACE. (SEE PICTURE 4).
- FEED THE WIRES THROUGH HOLE IN UNDER-TRAY AND ROUTE AS ORIGINAL AND RECONNECT WIRING PLUG. IT IS A GOOD IDEA TO TEST ALL LIGHTS AT THIS STAGE.
- REFIT THE INDICATOR HOUSING.
- USING THE ORIGINAL BOLTS REFIT THE LICENCE PLATE BRACKET.
- REFIT AND SECURE PILLION SEAT COWL.
- REFIT PASSENGER SEAT.
- REFIT RIDER SEAT.
- REFIT LICENCE PLATE (IT MAY REQUIRE DRILLING).
- **IMPORTANT: IF FITTING A FULL-SIZE LICENCE PLATE AND PLACING IT FAR DOWN ON THE LICENCE PLATE HANGER, THERE IS A SMALL CHANCE OF THE LICENCE PLATE HITTING THE BACK WHEEL UNDER HEAVY LOAD AND OVER LARGE BUMPS IN THE ROAD. IT IS YOUR RESPONSIBILITY TO CHECK FOR THIS POSSIBILITY AND TAKE AVOIDING ACTION. FAILURE TO CHECK THIS COULD RESULT IN SERIOUS INJURY.**
- DEPENDING ON LOCAL LAWS, ATTACH ENCLOSED REFLECTOR IN AN APPROPRIATE LOCATION.
- RECHECK THE LICENCE PLATE ILLUMINATOR AND ALL LIGHTS BEFORE RIDING.

ISSUE 1 03/03/2011 (NSY)

R&G Racing
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



FRANCE
INSTRUCTIONS DE MONTAGE DU SUPPORT DE PLAQUE LP0102BK
SUZUKI GSX-R600 2011

VERIFIER QUE TOUTES LES PIECES PRESENTEES SUR LA PHOTO PRINCIPALE
SOIT PRESENTEES DANS LE KIT DE MONTAGE.
LIRE TOUTE LA NOTICE AVANT DE COMMENCER LE MONTAGE.

LEGENDE

- ARTICLE 1 = Support de plaque (TB0102) (x1).
ARTICLE 2 = Connecteurs électrique
ARTICLE 3 = Lumière de plaque (LA0002) (x1).
ARTICLE 4 = Couvercle de Lumière (LH0004) (x1).
ARTICLE 5 = Tube en caoutchouc thermo-rétractable 150mm (x1).
ARTICLE 6 = Réflecteur (x1).
ARTICLE 7 = Clips pour câbles (x2).

OUTILS NECESSAIRES

- Jeu de clé Allen (incluant les clés de 4 et 5mm).
 - Jeu de clef 6,10 et 12 mm
 - Tournevis plat
 - Pince d'électricien
 - Super glue.

Instructions de montage

- Enlevez la selle
- Enlevez la selle passager.
- Enlevez les vis de fixation du carénage de selle arrière et enlevez le carénage.
- Pour avoir accès à la prise électrique de l'éclairage de plaque d'origine, enlevez le logement du clignotant droit. (voir photo 2)
- Déconnectez la prise de l'éclairage de plaque.
- Enlevez les 4 vis qui retiennent le support de plaque à la moto. (voir photo 1) et retirez celui ci en faisant attention de ne pas abimer les câbles. (attention voir photo 3)
- Fixez le nouvel éclairage de plaque sur le support R&G. (photo 4)
Nous vous suggérons de couper et de réutiliser les prises électriques d'origine.
Protégez la nouvelle connection à l'aide de la gaine en caoutchouc thermo rétractable. (Livrée dans le kit)
Sens du montage des fils
Origine Gris--→R&G Rouge
Origine Noir/Blanc--→R&G Noir
- **MERCI DE NOTER QUE VOUS DEVREZ COLLER LA PIECE N°4 A L'ECLAIRAGE DE PLAQUE R&G A L'AIDE DE COLLE SUPER GLUE. (voir photo 4)**
- Glissez les câbles de l'éclairage de plaque à travers le trou (voir photo 4)



- Glissez ensuite les câbles à travers le trou dans le passage de roue de la moto et remplacez les câbles comme à l'origine.
- Testez l'éclairage de plaque à ce moment du montage
- Remplacez le logement du clignotant Droit
- Fixez le support sur la moto à l'aide des 4 vis d'origine.
- Remplacez et fixez le carénage
- Remontez la selle passager et pilote.
- Remontez la plaque d'immatriculation –Percer si nécessaire.
- **IMPORTANT: Veiller à toujours placer la plaque d'immatriculation le plus haut possible sur le support, ceci pour éviter tout contact entre la plaque et le pneu.**
- Vérifiez que l'éclairage de plaque fonctionne correctement.